

one

Touch Computers



FRONT: 19" touch screen PC
Model: ONE191 ITSPC



- 4 in 1 Card Reader
- IEEE1394 x2
- Audio x3
- USB x5

SIDE: 19" touch screen PC
Model: ONE191 ITSPC



UNDERSIDE: 19" touch screen PC
Model: ONE191 ITSPC

- Exterior Monitor
- Serial
- USB x2
- LAN
- Keyboard
- Mouse
- Power

1-877-79 TOUCH

www.myone.ca

one

Touch Computers

Touch Screen 19"CPU Specifications

Product	• ONE-191 ITSPC
CPU	• Intel® Core™ Duo/Dual Core 1.8 GHz
Chipset	• North Bridge Intel® 945G Express Chipset • South Bridge Intel® ICH7
Memory	• 2x DDF II DIMM memory slots (2GB memory) • Supports 1.8V DDR II DIMM • Supports dual channel DDR II 667/533/400 DIMM
HDD	• 3.5" size SATA II (250GB)
Optical Device	• DVD±RW
Display Resolution	• 19" TFT LCD (SXGA 1280 x 1024)
Expansion Slots	• 2x mini PCI slot (internal slot)
Audio	• Built-in 2x speakers (3W) • Realtek ALC655 6-channel AC'97 Rev2.3 CODEC
LAN	• Marvell 88E8053 controller supporting 10/100/1000 BASE-T Ethernet
USB Port	• Max 6x USB 2.0 ports
VGA Port	• Intel® 945G built-in experience superior graphics with Intel® GMA950
Multi-Media Card Reader	• SD / MS / MMC / x D
Back Panel I/O Ports	• 1x Power Connector, 1x PS/2 Keyboard, 1x PS/2 Mouse, 1x RJ45, 2x USB 2.0, 1x Serial, 1x VGA,
Side Panel I/O Ports	• 4x USB, 3x Audio, (Line In / Line Out / MIC), 2x IEEE 1394, Card Reader
Wireless LAN	• 32 bit Mini-PCI card Interface, Support 64 and 128 bit WEP encryption • 802.11b : 11Mbps up to 180m (Outdoor), 35-60m (Indoor) • 802.11g : 54Mbps up to 50m (Outdoor), 20m (Indoor)
Touch Screen	• Internal RS-232 for Touch Screen Control Board • 19", 5 wire resistive touch screen
Fan Speed Control	• The CPU fan speed can be set by temperature of CPU
Watch Dog	• Can be set by 500ms, 1,2,4 seconds period. RESET or NMI was generated when CPU did not periodically trigger the timer
Power Lost Recovery	• System will auto power on during a power failure
Power Adapter	• Input : AC / 100-240V (50/60Hz) 2.5A • Output : DC / 20V, 9A 180W

www.myone.ca

1-877-79 TOUCH